

Uniquely creative, uniquely responsive to your needs.

MOBILE PRINTER

SM2-41

4" MOBILE LABEL PRINTER

Features

- 150mm/sec. printing speed
- Drop-in paper loading system
- Robust body
- Receipt and Peel-off model available
- Various interface (Serial, USB, IrDA, BT and WiFi)
- Energy saving system (Auto power off)
- Workable for battery and AC adapter



SM2-41L(Peel-off)



SM2-41(Receipt)



SANEI ELECTRIC INC.

Phone 03-3986-1188 www.sanei-elec.co.jp

SM2-41

Features

- High speed printing at 150mm/sec.
- Drop-in paper loading and large capacity paper bucket
- Adjustable paper width (50mm to 115mm)
- Various interface (Serial, USB, IrDA, BT and WiFi)
- Large battery capacity
- Receipt and Peel-off model available
- Rugged drop resistant design

Applications

- Logistics (Barcode label)
- Receipt and Ticket
- Medical and Inspection label
- Maintenance and Field service

Accessories

- AC adapter
- Li-ion battery
- Shoulder strap



| Model | | Peel-off model | Receipt model |
|------------------------|-----------|--|-----------------------|
| Printing method | | Direct line thermal | |
| Resolution | | 203dpi (8dot/mm) | |
| Number of dots | | Max.832dots/mm | |
| Printing width | | Max.104mm | |
| Printing speed | | Max.150mm/sec. (Peel-off mode : Max.80mm/sec.) | Max.150mm/sec. |
| Paper | Style | Label paper/Receipt paper | |
| | Type | Roll paper/Fanfold paper | |
| | Width | 50 to 115mm | |
| | OD | Max. ϕ 58mm | |
| | Thickness | 0.059 to 0.16mm | |
| Character font | | 9x16, 12x24 | |
| Character type | | Alphanumeric, PC437/850/852/857/858/860/863/865/866, WPC1252 | |
| Peel-off operation | | Equipped | None |
| Tear bar | | Plastic | Metal |
| Paper sensor | | Black mark, Label gap, Peel-off | Black mark, Label gap |
| Paper loading | | Drop-in paper loading | |
| Interface | | RS232C+USB2.0, IrDA, BT / WiFi (option) | |
| Emulation | | ESC/POS conformity, Label mode | |
| Barcode | | UPC-A/E, JAN 13/8, CODE 39, ITF, CODA BAR, CODE 93, QR code/PDF417 | |
| Power supply | | Li-ion rechargeable battery (14.8V/2200mAh) / AC adapter | |
| Battery charge | | Internal battery charger | |
| Paper guide | | Adjustable paper guide at free position | |
| Reliability | | Thermal head : 100Km/100million pauses (at receipt paper) | |
| Fall impact resistance | | 1m | |
| Operating condition | | -15 to 50°C | |
| Dimensions | | 157(W)x138.6(D)x67(H)mm | |
| Weight | | Approx. 780g (included battery, without roll paper) | |
| Safety standards | | VCCI, CE, FCC | |

*ESC/POS is registered trademark of Seiko Epson Corporation.

*All specifications are subject to change without notice.

Distributed by

 **SANEI ELECTRIC INC.**
www.sanei-elec.co.jp

Headquarters :

5F, Taisou-Ikebukuro Building, 2-61-1 Ikebukuro, Toshima-ku, Tokyo 171-0014, Japan
Phone: 81-3-3986-1188 Fax: 81-3-3988-5876

