

BL-112 II



Features

- Printing speed Max.80mm/sec.
- Label printing
- Barcode including 2 dimensional barcode
- Page mode print function
- Form overlay function
- Bluetooth® model (BL-112BT)



Printer model

Specifications

| Model | BL-112 II PS | BL-112 II UI | BL-112 II BT |
|-----------------------------------|--|----------------------|------------------------|
| Printing method | Direct line thermal | | |
| Number of dots | 832dots | | |
| Resolution | 8 dots/mm | | |
| Printing/ Paper width | 104mm/112mm | | |
| Printing speed | 80mm/sec max * Using AC adapter | | |
| Character dot matrix (HxW) | 24x12dots , 16x8dots , 24x24dots , 16x16 dots | | |
| Character size (HxW) | 3.0x1.5mm , 2.0x1.0mm , 3.0x3.0mm , 2.0x2.0mm | | |
| Characters/line | 69 characters/line (24 dots、 at space 0 dot) | | |
| Interface | RS-232C , Centronics | USB , IrDA (IrOBEX) | Bluetooth1.1 , RS-232C |
| Input buffer | 1024 bytes | | |
| User memory | 8192 bytes | | |
| EMI conformity | VCCI classB , FCC classB , CE | VCCI classB | |
| Power supply | DC8.7V (AC adapter · BLS-100W) | | |
| Bundled items | AC adapter · BLS-100W , AC power cord · ACS-100J , sample roll paper | | |

Option

| | |
|---------------------------------------|------------------------|
| Thermal paper (width · Length) | P-112-30 (112mm · 30m) |
|---------------------------------------|------------------------|

* Specifications is subject to be changed for improvement without notice.

