

2INCH PANEL PRINTER

PORTI-P30, P40/PP40, P60/PP60



Porti-P30




Porti-P40/PP40



Porti-P60/PP60

Applications

Test & Measurement, Transportation, Health care, ATM, Coupon, Self service, Kiosks, Electronic voting systems.



Features

- Ultra small size rack mount printer.
- Very silent printing thru direct thermal printing method
- High speed(50mm/sec)
- UART or TTL, Parallel(PP40, PP60 only) interface.
- Support text and graphic printing.
- Support bit-image (logo) download.
- Easier paper loading by CLAMSHELL design.
- Easier maintenance with self-diagnostics.

Specification

Model	P30	P40 / PP40	P60 / PP60
Printing method	Direct thermal line printing		
Characters per line	42cpl (MAX)		
Characters size	Eng : 9x24 dots, 12x24 dots Kor : 16x24 dots [24x24 dots]		
Optional Characters	Simplified/Traditional Chinese, Arabic, Cyrillic, Russian, Turkish, Greek, Japanese, Persian, Latin9 and Others upon request.		
Resolution	203 dpi, 8 dots/mm		
Print width	2-inch (48mm, 384 dots)		
Printing speed	50 mm/sec (MAX)		
Dimensions	75 x 55 x 30.3mm	80 x 75 x 40mm	76 x 93 x 62mm
Weight	83g	P40 :96g, PP40 : 108g	P60 : 125g, PP60 : 136g
Interface	· P30, P40, P60 : UART(RS-232C or TTL) · PP40, PP60 : UART or Parallel		
Paper supplied	Thermal roll paper (57mm wide, 30Ø)	Thermal roll paper (57mm wide, 40Ø)	Thermal roll paper (57mm wide, 60Ø)
	Paper thickness : 60±5µm		
Barcodes	1-dimension:Code128, EAN 128, Code39, I2/5, Code93, UPC, EAN, KAN, JAN, CODABAR 2-dimension:PDF417, QR Code, DATA Matrix		
Driver	Microsoft Windows XP / VISTA / 7 , Windows CE, Linux, Android OS driver compatible		
Input power	5VDC, Standby 60mA and MAX 2.5A (P30, P40) 9VDC, Standby 60mA and MAX 3A (Standard model) 12~24VDC, Standby 60mA and MAX 3A (PP40, PP60)		

Small size panel printer

